

## AC/DC Digital Clamp Meters

# MODEL 2010



- High sensitivity, miniature AC/DC clamp meter.
- 0.1mA minimum resolution for AC current and 1mA minimum resolution for DC current.
- Output terminal for recorder connection.



Never make current measurement on a circuit above 60V AC/DC as the instrument is designed for use on low voltage circuits only.

AC A	200mA/2/20A ±1%rdg±2dgt [50/60Hz] (200mA) ±1.5%rdg±8dgt [40Hz - 2kHz] (200mA) ±1%rdg±2dgt [50/60Hz] (2A) ±2.5%rdg±10dgt [40Hz - 2kHz] (2/20A)
DC A	2/20A ±1%rdg±2dgt (2A) ±1.5%rdg±4dgt (20A)
Conductor size	Ø7.5mm max.
Frequency response	DC, 40Hz - 2kHz
Output	Recorder : DC200mV against AC200mA/2/20A DC200mV against DC2/20A
Power source	6LF22(9V) × 1 or AC Adaptor
Dimensions	142(L) × 64(W) × 26(D)mm 153(L) × 23(W) × 18(D)mm Clamp Sensor
Weight	220g approx.
Included Accessories	9071 (Carrying Case) Alkaline 6LF22 × 1 Instruction Manual
Optional Accessories	8022 (AC Adaptor) (110V) 8023 (AC Adaptor) (220V) 7256 (Output cord)