

TDR500/3

Handheld TDR



- **Simple operation**
- **AUTO set up for instant use**
- **Ultra fast pulse for near end fault identification**
- **Trace HOLD feature**
- **IP54 rating offers real life working**
- **Designed for use on all metallic cable pairs**

DESCRIPTION

The TDR500/3 is a hand held, compact Time Domain Reflectometer for locating faults on metallic cables. It has a minimum resolution of 0.1 m/0.3 ft and a 5 km/15 kft maximum range depending on velocity factor selected and cable type.

Four output impedances are available (25, 50, 75, and 100 Ω) and a velocity factor between 0.2 and 0.99 will meet any cable test requirements

The TDR500/3 has a simple selection option which together with a 4 way control switch offers an intuitive operation for the user.

- Power blocking filter not required
- Environmental protection to IP54
- 2ns pulse for near end fault location
- AUTO option selecting gain and pulse for each range
- Display distance in metres or feet
- Uses five AA (LR6) primary cells

FEATURES

An AUTO selection option ensures that the most effective parameters are selected depending on the range required, aiding rapid diagnosis of the TDR trace. A clear operator controlled cursor allows instant measurement of the distance to the fault.

A trace HOLD feature also allows the operator to hold a trace on the screen, something not seen on most other handheld TDRs. Extra high resolution together with white-light backlight and grey scale tones give the graphical display a vibrancy, aiding the user in identifying key events on the trace.

- Backlit graphics monochrome LCD (256 x 128)
- Adjustable display contrast
- Resolution to 0.1 m
- For use on Telecom TNV-3 circuit, or 150V CAT IV power circuits

SPECIFICATIONS

Except where otherwise stated, this specification applies at an ambient temperature of 20 °C.

General

Ranges	10 m, 25 m, 100 m, 250 m, 1000 m, 2500 m, 5000 m (30 ft, 75 ft, 300 ft, 750 ft, 3000 ft, 7500 ft, 15000 ft)
Accuracy:	±1% of range ± pixel at 0.67 VF [Note- The measurement accuracy is for the indicated cursor position only and is conditional on the velocity factor being correct.]
Resolution:	1% of range
Input protection:	This instrument complies with IEC61010-1 for connection to live systems up to 150 V CAT IV when used with the optional fused test lead set.
Output pulse:	5 volts peak to peak into open circuit. Pulse widths determined by range and cable
Gain:	Set for each range with three user selectable steps (in manual operating mode)
Velocity factor:	Variable from 0.2 to 0.99 in steps of 0.01
TX null:	Automatic
Power down:	Automatic after 5 minutes with no key press
Backlight:	Stays on for 1 minute with no key press
Batteries:	Five LR6 (AA) type batteries, Manganese alkali or nickel metal-hydride cells
Battery life:	Up to 14 hours (typical)
Mechanical:	The instrument is designed for use indoors or outdoors and is rated to IP54.

Case dimensions:	230 mm (9 in) x 115 mm (4.5 inches) x 48 mm (2 inches)
Instrument weight:	0.6 kg (1.32 lbs)
Case material:	ABS
Connectors:	Two 4 mm-safety terminals
Test leads (TDR500/3):	2 metres long consisting of 2 x 4 mm shrouded connector to miniature crocodile clips
Display:	256 x 128 pixel Graphics LCD
Environmental	
Operating temperature	-15 °C to +50 °C (5 °F to 122 °F)
Storage temperature:	

ORDERING INFORMATION

Item (Qty)	Cat. No.
Included accessories	
Time Domain Reflectometer	1002-227
Included accessories	
Hard carry case	5410-420
Miniature clip test lead set	6231-652
User guide CD	2002-178
Optional accessories	
Fused test lead set	1002-015